

## INTELLIGENT SELECTION OF MESSAGE DELIVERY MECHANISM

### Reference to Related Applications

[0001] This application is a continuation-in-part of:

- i. PCT Patent Application PCT/US03/14041, filed on 6 May 2003, Attorney Docket 630-035pct, entitled "Intelligent Selection of Mode of Communication," now pending, which is itself a continuation-in-part of:
  - ii. U.S. provisional patent application serial number 60/380140, filed on 5/6/2002, Attorney Docket 630-007us, entitled "Method For Interception, Manipulations, and Usage of Bluetooth Voice Streams," now expired.
- Both of these applications are incorporated by reference.

### Field of the Invention

[0002] The present invention relates to telecommunications in general, and, more particularly, to intelligent selection of a delivery mechanism for sending a message from a telecommunications terminal.

### Background of the Invention

[0003] Figure 1 depicts a schematic diagram of wireless local-area network 100 in the prior art, which comprises: stations 101-1 through 101- $N$ , wherein  $N$  is a positive integer, and access point 102, interconnected as shown. Each station 101- $i$ , wherein  $i$  is a positive integer in the set  $\{1, \dots, N\}$ , communicates wirelessly with other stations in local-area network 100 via access point 102. Station 101- $i$  must be located within a particular distance from access point 102 in order to communicate with access point 102 and other stations in wireless local-area network 100. A popular standard for wireless local-area networks is the Institute of Electrical and Electronics Engineers (IEEE) 802.11 specification.

[0004] Figure 2 depicts a schematic diagram of two cellular handsets 201-1 and 201-2 that transmit and receive signals via cellular wireless network 200. As shown in Figure 2, wireless network 200 comprises  $M$  wireless switching centers 210-1 through 210- $M$ , where  $M$  is a positive integer, and wireless switching center 210-3 communicates with  $K$  base stations 220-3-1 through 220-3- $K$ , where  $K$  is a positive integer. Each wireless switching center 210- $i$  in wireless network 200 typically is connected to a plurality of base stations;

however, for the purpose of clarity, base stations are shown only for wireless switching center 210-3 in Figure 2.

**[0005]** A hybrid 802.11/cellular telecommunications terminal is a terminal that has both an IEEE 802.11 radio and a cellular radio (*e.g.*, a Code Division Multiple Access radio, *etc.*), and therefore can send and receive signals either via an IEEE 802.11 local-area network or a cellular network.

### **Summary of the Invention**

**[0006]** The present invention enables the advantageous selection of a delivery mechanism for sending a message from a hybrid telecommunications terminal. For the purpose of this specification, a delivery mechanism comprises at least one of:

- (i) a physical medium (*e.g.*, copper, radio, *etc.*),
- (ii) a physical layer protocol (*e.g.*, Direct Sequence Spread Spectrum [DSSS], *etc.*),
- (iii) a medium access control (*e.g.*, Code Division Multiple Access [CDMA], *etc.*), and
- (iv) a network for transport (*e.g.*, Public Switched Telephone Network [PSTN], Internet, *etc.*).

Naturally, no selection is required for a particular category if only one choice is available (*e.g.*, if radio is the only available physical medium, *etc.*).

**[0007]** In particular, the illustrative embodiment enables the automatic selection of a delivery mechanism for a message sent from a first terminal to a second terminal based on at least one of:

- (i) the location of the first terminal,
- (ii) the location of the second terminal,
- (iii) the time and date (*i.e.*, the *calendrical* time) at the first terminal,
- (iv) the calendrical time at the second terminal, and
- (v) one or more properties of the message (*e.g.*, the sending user, the receiving user, a message priority, the contents of the message, *etc.*).

The following examples illustrate the desirability of automatic selection of a delivery mechanism based on (i) through (v) above.

**[0008] Example for (i):** At certain locations in a hospital, placing a telephone call via a cellular phone might have deleterious effects on nearby medical equipment, while placing a telephone call via an IEEE 802.11 station might not interfere with the medical equipment

(for example, because the 802.11 radio operates at a different frequency). Conversely, in an 802.11 "hotspot" (*i.e.*, an 802.11 local-area network in a public location) it might be more desirable to send an email message via a cellular network than via the hotspot, since encryption and security typically are more robust in cellular networks. Thus, it would be advantageous to have automatic selection of the most desirable delivery mechanism for sending a message from a hybrid telecommunications terminal, where "most desirable" is based on the location of the terminal in combination with particular preferences (*e.g.*, user-defined rules, *etc.*).

**[0009] Example for (ii):** An administrator in building A of a hospital places a call with a hybrid 802.11/cellular phone to a nurse in building B of the hospital, who also has a hybrid 802.11/cellular phone. Building B contains sensitive medical equipment, while building A does not. It would be advantageous if the call to the nurse were automatically transmitted over the hospital campus 802.11 local-area network, rather than a cellular network, when the nurse is in building B. Conversely, when the nurse is in building A, it might be more desirable for the call to be transmitted over a cellular network for increased security (*e.g.*, to comply with federal privacy laws when discussing a patient's records, *etc.*)

**[0010] Example for (iii):** An employee places a telephone call via a hybrid 802.11/cellular phone from his or her office. The corporate 802.11 local-area network is connected to the Internet via a voice-over-Internet-Protocol (VoIP) gateway. It might be advantageous for calls to be transmitted via 802.11 and the Internet rather than via a cellular network during business hours when cellular "air time" is more expensive than landline telephone charges. Conversely, for an employee that works the night-shift or weekend-shift, it might be advantageous for calls to be transmitted by a cellular network when the cellular service provider offers "free nights and weekends."

**[0011] Example for (iv):** In the example for (iii), if the employee is in New York and places a telephone call at 9:00 PM Eastern Standard Time to a person in San Francisco, it might be desirable to transmit the call over the 802.11 local-area network and Internet, rather than a cellular network, if the San Franciscan's cellular plan charges for incoming calls during peak periods (such as 6:00 PM Pacific Standard Time).

**[0012] Examples for (v):**

- Bob, who works for a defense contractor, places a telephone call via a hybrid 802.11/cellular phone to Colonel Flag, the Army representative on the corporate premises. Since the call is directed to Colonel Flag, the call should be transmitted over a cellular network for greater security.

- Bob sends a high-priority unclassified email message to a co-worker using a hybrid telecommunications terminal. Bob's cellular provider's email system is not very reliable, and thus the email message is automatically sent via the corporate 802.11 local-area network, since reliability, and not security, is the most important criterion for a high-priority unclassified message.
- Colonel Flag has a hybrid telecommunications terminal that can communicate either via a military satellite-based network, or a civilian cellular network. The terminal supports both voice and data communications, and has an operating system that requires a user to log in with a password. Colonel Flag's wife, who is a civilian, also has an account on this terminal. When Colonel Flag sends a message from the terminal, the message is automatically transmitted either via the satellite network or the cellular network, depending on the terminal's location and/or the calendrical time, as described above. When Colonel Flag's wife logs into the terminal and sends a message, however, the message is always transmitted via the civilian cellular network.
- Colonel Flag sends an email message from the hybrid satellite/cellular telecommunications terminal to Colonel Blake. Based on the text of the message, the message is automatically transmitted either via the cellular network (*e.g.*, the email discusses yesterday's Army-Navy football game, *etc.*) or the satellite network (*e.g.*, the email discusses a planned military operation, *etc.*).

**[0013]** For the purposes of this specification, the term "calendrical time" is defined as indicative of one or more of the following:

- (i) a time (*e.g.*, 16:23:58, *etc.*),
- (ii) one or more temporal designations (*e.g.*, Tuesday, Novemeber, *etc.*),
- (iii) one or more events (*e.g.*, Thanksgiving, John's birthday, *etc.*), and
- (iv) a time span (*e.g.*, 8:00-9:00, *etc.*).

**[0014]** The illustrative embodiment comprises: (a) determining the location of a first telecommunications terminal; and (b) selecting, based on the location, one of a plurality of physical media available to the first telecommunications terminal for sending a message to a second telecommunications terminal.

### **Brief Description of the Drawings**

[0015] Figure 1 depicts exemplary wireless local-area network 100 in the prior art.

[0016] Figure 2 depicts exemplary cellular network 200 and cellular handsets 201-1 and 201-2 in the prior art.

[0017] Figure 3 depicts the operation of hybrid telecommunications terminals 301-1 and 301-2 in accordance with the illustrative embodiment of the present invention.

[0018] Figure 4 depicts a block diagram of the salient components of hybrid telecommunications terminal 301-*i*, as shown in Figure 3, in accordance with the illustrative embodiment of the present invention.

[0019] Figure 5 depicts a flowchart for selecting a physical medium, a physical layer protocol, a network, and a medium access control for sending a message from hybrid telecommunications terminal 301-*i*, as shown in Figure 3, in accordance with the illustrative embodiment of the present invention.

### **Detailed Description**

[0020] Figure 3 depicts a schematic diagram of in accordance with the illustrative embodiment of the present invention. Figure 3 depicts wireless local-area network 300 centered at access point 302, cellular network 310, hybrid telecommunications terminals 301-1 and 301-2, Internet 303, and Public Switched Telephone Network (PSTN) 304, interconnected as shown.

[0021] Cellular network 310 is identical to cellular network 200, as depicted in Figure 2.

[0022] Access point 302 is identical to access point 202, as depicted in Figure 2. As shown in Figure 3, access point 302 is connected to Internet 303 and Public Switched Telephone Network (PSTN) 304, thereby enabling stations in local-area network 300 to send and receive signals via Internet 303 or Public Switched Telephone Network (PSTN) 304, in well-known fashion.

[0023] Hybrid telecommunications terminals 301-1 and 301-2 are 802.11/cellular telecommunications terminals. As shown in Figure 3, both telecommunications terminals 301-1 and 301-2 are within transmission range of cellular network 310. Hybrid telecommunications terminal 301-1 is also within transmission range of access point 302, and thus has the capability of sending and receiving signals via local-area network 300 as well as cellular network 310. Hybrid telecommunications terminal 301-2, however, is

outside transmission range of access point 302 and thus can send and receive signals only via cellular network 310.

**[0024]** As will be clear to those skilled in the art, Figure 3 illustrates merely one embodiment in which a hybrid telecommunications terminal might be able to send messages via a plurality of delivery mechanisms in accordance with the present invention. In the example of Figure 3, hybrid telecommunications terminal 301-1 can send messages via two different wireless networks (*i.e.*, wireless local-area network 300 and cellular network 310.) In some other embodiments, hybrid telecommunications terminal 301-1 might be able to send messages (i) via three or more different networks; (ii) via two or more different physical media (*e.g.*, copper, radio, *etc.*); (iii) via two or more different medium access controls (*e.g.*, Code Division Multiple Access, Time Division Multiple Access, *etc.*); or (iv) via two or more different physical layer protocols (*e.g.*, Direct Sequence Spread Spectrum, Orthogonal Frequency Division Multiplexing, *etc.*). It will be clear to those skilled in the art, after reading this specification, how to make and use embodiments of the present invention for such alternatives.

**[0025]** Figure 4 depicts a block diagram of the salient components of hybrid telecommunications terminal 301-*i* in accordance with the illustrative embodiment of the present invention. Hybrid telecommunications terminal 301-*i* comprises receiver 401, processor 402, memory 403, transmitter 404, and clock 405, interconnected as shown.

**[0026]** As shown in Figure 4, receiver 401 receives signals from a plurality of networks, including satellite-based, cellular, and wireless local-area networks. As will be appreciated by those skilled in the art, in some embodiments of the present invention receiver 401 might be a single physical receiver (*e.g.*, a radio, *etc.*) for receiving signals from different networks, while in some other embodiments receiver 401 might be a composite receiver comprising a plurality of physical receivers (*e.g.*, a radio and an Ethernet network interface card, two different radios, *etc.*).

**[0027]** Processor 402 is a general-purpose processor that is capable of executing instructions stored in memory 403, of reading data from and writing data into memory 403, of generating messages, and of executing the tasks described below and with respect to Figure 5, described below. In some alternative embodiments of the present invention, processor 402 might comprise one or more special-purpose processors (*e.g.*, a network processor, a dedicated processor for determining location from satellite signals, *etc.*). In either case, it will be clear to those skilled in the art, after reading this disclosure, how to make and use processor 402.

**[0028]** Memory 403 stores data and executable instructions, as is well-known in the art, and might be any combination of random-access memory (RAM), flash memory, disk drive, *etc.*

**[0029]** As shown in Figure 4, transmitter 404 transmits signals to a plurality of networks, including satellite-based, cellular, and wireless local-area networks. As will be appreciated by those skilled in the art, in some embodiments of the present invention transmitter 404 might be a single physical transmitter (*e.g.*, a radio transmitter, *etc.*) for transmitting signals via different networks, while in some other embodiments transmitter 404 might be a composite transmitter comprising a plurality of physical transmitters (*e.g.*, a radio transmitter and an Ethernet network interface card, two different radio transmitters, *etc.*).

**[0030]** Clock 405 transmits the current date and time to processor 402 in well-known fashion.

**[0031]** Figure 5 depicts flowchart 500 for selecting a physical medium, a physical layer protocol, a network, and a medium access control for sending a message from hybrid telecommunications terminal 301-*i* in accordance with the illustrative embodiment of the present invention. As disclosed in the illustrative embodiment processor 402 of hybrid telecommunications terminal 301-*i* executes the tasks of flowchart 500; however, it will be clear to those skilled in the art how to make and use alternative embodiments of the present invention in which another entity (*e.g.*, an Internet server, an access point, a wireless switching center, *etc.*) performs some or all of the tasks of flowchart 500 (*i.e.*, "infrastructure-based" embodiments).

**[0032]** At task 510, a signal to send a message *M* from hybrid telecommunications terminal 301-*i* to some other telecommunications terminal *T* (not necessarily hybrid) is received in well-known fashion. In the illustrative embodiment, processor 402 receives this signal (*e.g.*, from a user input device [not shown in Figure 4], *etc.*), while in some other embodiments, another entity (*e.g.*, an Internet server processor, an access point processor, *etc.*) might receive this signal.

**[0033]** At task 520, the location of hybrid telecommunications terminal 301-*i* is determined. In the illustrative embodiment, satellite signals received by receiver 401 are forwarded to processor 402, and processor 402 performs the necessary computations to determine the location of hybrid telecommunications terminal 301-*i*. In some other embodiments, hybrid telecommunications terminal 301-*i* might have a dedicated Global Positioning System (GPS) processor for determining location, as is well-known in the art,

while in some other embodiments, another entity such as a wireless base station might determine the location of hybrid telecommunications terminal 301-*i*.

**[0034]** At optional task 530, the location of hybrid telecommunications terminal *T* is determined. (In some embodiments it might not be desirable to implement task 530 [e.g., it might require too many changes to legacy equipment, *etc.*] and thus this task is depicted as optional via dotted lines.) In the illustrative embodiment, hybrid telecommunications terminal 301-*i* determines the location of hybrid telecommunications terminal *T* by sending a query to the appropriate access point, server, wireless base station, *etc.* In some other embodiments, an access point, server, *etc.* might perform task 530, possibly in addition to task 520, as described above. It will be clear to those skilled in the art how to implement task 530 in accordance with the illustrative embodiment, or in accordance with alternative embodiments such as infrastructure-based implementations.

**[0035]** At task 540, the calendrical time at hybrid telecommunications terminal 301-*i* is determined. In the illustrative embodiment, processor 402 receives this information from clock 405. In some other embodiments, processor 402 might receive this information from receiver 401, which in turn receives this information from another entity (e.g., a wireless base station, *etc.*). In some other infrastructure-based embodiments, the wireless base station, access point, *etc.* that performs some or all of the tasks of flowchart 500 performs task 540 (e.g., via its own clock, *etc.*)

**[0036]** At optional task 550, the calendrical time at telecommunications terminal *T* is determined. In the illustrative embodiment, processor 402 determines the calendrical time at hybrid telecommunications terminal *T* mathematically based on the results of task 530 and 540 (*i.e.*, by determining the number of time zones separating terminals 301-*i* and *T* and accordingly adding or subtracting hours from the calendrical time determined at task 540.) In some other embodiments, an access point, server, *etc.* might perform task 550. It will be clear to those skilled in the art how to implement task 550 in accordance with the illustrative embodiment, or in accordance with alternative embodiments such as infrastructure-based implementations.

**[0037]** At task 560, one or more properties of message *M* (e.g., priority, semantic content, the sending user, the receiving user, *etc.*) are determined in well-known fashion. In the illustrative embodiment processor 402 performs task 560, while in some other embodiments an access point, server, *etc.* might perform task 560.

**[0038]** At task 570, a physical medium is selected from the set of physical media available to hybrid telecommunications terminal 301-*i* for sending message *M*. (This set is



based on transmitter 404's capabilities and terminal 301-*i*'s location). The selection is based on one or more of the location(s), calendrical time(s), and properties obtained in tasks 520 through 560, in accordance with one or more rules. In the illustrative embodiment task 570 is performed by processor 402, while in some other embodiments an access point, server, *etc.* might perform task 570. As will be appreciated by those skilled in the art, the rules for selecting a physical medium might be hard-coded (*e.g.*, stored in a read-only portion of memory 403, *etc.*), or might be defined by the user of terminal 301-*i* (*e.g.*, via input means of terminal 301-*i*, *etc.*).

**[0039]** At task 580, a network is selected from the set of networks available to hybrid telecommunications terminal 301-*i* for sending message *M*. (This set is based on the physical medium selected at task 570, transmitter 404's capabilities, and terminal 301-*i*'s location). The selection is based on one or more of the location(s), calendrical time(s), and properties obtained in tasks 520 through 560, in accordance with one or more rules. In the illustrative embodiment task 580 is performed by processor 402, while in some other embodiments an access point, server, *etc.* might perform task 580. As described above, in some embodiments the rules for selecting a network might be hard-coded (*e.g.*, stored in a read-only portion of memory 403, *etc.*), or might be defined by the user of terminal 301-*i* (*e.g.*, via input means of terminal 301-*i*, *etc.*).

**[0040]** At task 590, a physical layer protocol is selected from the set of physical layer protocol available to hybrid telecommunications terminal 301-*i* for sending message *M*. (This set is based on the network selected at task 580, transmitter 404's capabilities, and potentially terminal 301-*i*'s location). The selection is based on one or more of the location(s), calendrical time(s), and properties obtained in tasks 520 through 560, in accordance with one or more rules. In the illustrative embodiment task 590 is performed by processor 402, while in some other embodiments an access point, server, *etc.* might perform task 590. As described above, in some embodiments the rules for selecting a network might be hard-coded (*e.g.*, stored in a read-only portion of memory 403, *etc.*), or might be defined by the user of terminal 301-*i* (*e.g.*, via input means of terminal 301-*i*, *etc.*).

**[0041]** At task 595, a medium access control is selected from the set of medium access controls available to hybrid telecommunications terminal 301-*i* for sending message *M*. (This set is based on the network and physical layer protocols selected at tasks 580 and 590, respectively, and the capabilities of the software stored in memory 403.) The selection is based on one or more of the location(s), calendrical time(s), and properties obtained in

tasks 520 through 560, in accordance with one or more rules. In the illustrative embodiment task 595 is performed by processor 402, while in some other embodiments an access point, server, *etc.* might perform task 595. As described above, in some embodiments the rules for selecting a network might be hard-coded (*e.g.*, stored in a read-only portion of memory 403, *etc.*), or might be defined by the user of terminal 301-*i* (*e.g.*, via input means of terminal 301-*i*, *etc.*).

**[0042]** It is to be understood that the above-described embodiments are merely illustrative of the present invention and that many variations of the above-described embodiments can be devised by those skilled in the art without departing from the scope of the invention. It is therefore intended that such variations be included within the scope of the following claims and their equivalents.

**[0043]** What is claimed is: